



Electric Heating Capacities:

(When combined with the Duotec Air Handler)

05kW @ 240 volts, 10kW @ 240 volts & 15 kW @ 240 volts.

(Additional heating capacities also available when not using Duotec Air Handler. Please contact Parlay for more information).

Cooling Capacities:

12,000, 18,000, 24,000, 28,000 & 36,000 Btu/Hr.

Gas Heating Capacities:

(When combined with the Chinook Gas Furnace)

Heating Btu/Hr @ 95+ AFUE
15,000, 30,000, 45,000 & 60,000 2-stage variable condensing furnace.

- Cased coil with piston metering device.
- Internal multi-tap step down transformer & 230-volt primary to 115 volt secondary (*gas models only*).
- Little to no interior or exterior wall modifications are required in most applications.
- 10-year* parts warranty on gas heating components.
- 5-year* parts warranty on electric heating components.
- 2-year* parts warranty on air conditioning components.
- Increased efficiencies on gas and electricity.
- Electrically certified for installation & operation in the USA and Canada.

* complete warranty information available upon request.

R-SKYPAK GAS MODELS* OEM CROSS REFERENCE TABLE

**** XXXX *** ** *

• * = CONVERTIBLE RETURN (FIELD SELECTED BOTTOM OR SIDE)

• *** = VOLTAGE (12 = 208/230/1/60)

• * = UNIT RETURN AIR CONFIGURATION (L = LEFT HAND / R = RIGHT HAND)

• **** = RGAC / RGAD / SGAC / SGAD / SKYPAK I / SKYPAK II / SKYPAK III (C = R22 & D = R410A)

SKYMARK SKYPAK Model #	Heating Input BTU	Heating Output BTU (80 % AFUE)	Nominal Cooling Capacity	R-SKYPAK FURNACE (ECM – 2 Stage 94.5 % - 97.3 % AFUE)	Heating Input BTU	Low Heating Input BTU	High Heating Input BTU	R-SKYPAK Heating & Cooling Model #
**** 2012 *** ** *	20,000	16,000	12,000	C15-2-V	15,000	10,800	14,400	P-R-SKYPAK-12F15V-G
**** 4012 *** ** *	40,000	32,000	12,000	C30-2-V	30,000	11,540	28,860	P-R-SKYPAK-12F30V-G
**** 4018 *** ** *	40,000	32,000	18,000	C30-2-V	30,000	11,540	28,860	P-R-SKYPAK-18F30V-G
**** 6018 *** ** *	60,000	48,000	18,000	C45-2-V	45,000	30,240	43,200	P-R-SKYPAK-18F45V-G
**** 4024 *** ** *	40,000	32,000	24,000	C30-2-V	30,000	11,540	28,860	P-R-SKYPAK-24F30V-G
**** 6024 *** ** *	60,000	48,000	24,000	C45-2-V	45,000	30,240	43,200	P-R-SKYPAK-24F45V-G
**** 8024 *** ** *	80,000	64,000	24,000	C60-2-V	60,000	23,230	58,080	P-R-SKYPAK-24F60V-G
**** 6030 *** ** *	60,000	48,000	30,000	C45-2-V	45,000	30,240	43,200	P-R-SKYPAK-28F45V-G
**** 8030 *** ** *	80,000	64,000	30,000	C60-2-V	60,000	23,230	58,080	P-R-SKYPAK-28F60V-G
**** 8036 *** ** *	80,000	64,000	36,000	C60-2-V	60,000	23,230	58,080	P-R-SKYPAK-36F60V-G

* Above table based on R410A unit models.



R-SKYPAK EXCLUSIVE DISTRIBUTOR

FOR MORE INFORMATION PLEASE VISIT US AT: WWW.PARLAYHVACSOLUTIONS.COM

THE R-SKYPAK, ITS DESIGN AND DEVELOPMENTS ARE THE PROPERTY OF RANGER HEATING & AIR CONDITIONING PRODUCTS INC. ALL RIGHTS ARE RESERVED AND SHALL NOT BE USED OR REPRODUCED IN ANY WAY WITHOUT WRITTEN CONSENT OF RANGER HEATING AND AIR CONDITIONING PRODUCTS INC. PLEASE NOTE: DUE TO CONTINUING RESEARCH, DESIGN & PARTS AVAILABILITY, THIS INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE. E&OE.